

V-PLEX

Honeywell's patented V-Plex polling loop technology literally defines price and performance on a simple pair of wires. By utilizing only two wires instead of four, V-Plex offers significant advantages over conventional four-wire installations—providing economical expansion of peripheral devices and point identification to your central monitoring station.




4939SN

V-Plex Addressable Surface Mount Contact

- Programmable surface mount contact
- Compatible with control panels with serial number device capabilities for multiplex polling loop
- Standard gap: 1-1/4" (32mm)
- 5' (1.5m) CLII jacketed cable
- Epoxy sealed for protection from moisture and impact
- Programmed from VISTA keypad or learn mode

ALSO AVAILABLE:

- 4939SN-WH** – White
- 4939SN-BR** – Brown
- 4939SN-GY** – Grey



4945SN

V-Plex Addressable Surface Mount Contact

- Mini-surface style with snap on cover to conceal mounted screws
- Standard gap: 3/4" (19mm)
- 5' (1.5m) CL II jacket cable
- Epoxy sealed for protection from moisture and impact
- Programmed from VISTA keypad

ALSO AVAILABLE: 4945SN-WH – White



4944SN

V-Plex Addressable Recessed Mount Contact

- Popular press fit design conceals reed, Point ID module and magnet in just 3/8" (10mm) diameter case
- For use with VISTA controls supporting Point ID serial number sensors
- Standard gap: 3/4" (19mm) end-to-end
- Factory installed 5' (1.5m) zip cord lead saves time

ALSO AVAILABLE: 4944SN-WH – White



4191SN

V-Plex Recessed Magnetic Contact

- Programmable recessed contact with built-in RPM (Remote Point Module)
- Compatible with control panels with serial number device capabilities for multiplex polling loop
- Press fit design in 1/2" (12mm) diameter case
- Factory installed 5' (1.5m) zip cord leads saves time
- Standard gap: 7/8" (22mm) end-to-end

ALSO AVAILABLE:

- 4191SN-WH** – White
- 4191WA** – 3/4" (19mm) adapter for steel doors



4959SN

V-Plex Addressable Overhead Door Contact

- Rugged aluminum housing and adjustable L bracket type magnet
- Standard gap: 2" (51mm)
- 24" (61cm) armored cable
- Epoxy sealed for protection from moisture and impact
- Programmed from VISTA keypad

ALSO AVAILABLE:

- 4959SN** – Overhead Door Contact